

DESCRIPTION: **SK-250** is a light, yellowish-green, liquid chlorinated alkaline foam cleaner for cleaning in food processing plants.

DANGER: Contains caustic potash and Bleach. DO NOT mix with acids. Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Harmful if swallowed. Wear goggles and rubber gloves when handling. Avoid contamination of food. Remove and wash contaminated clothing. Do not breathe dust/fume/gas/mist/vapors/spray.

Do not Use SK-250 on aluminum or other soft metals.

STATEMENT OF PRACTICAL TREATMENT:

In case of contact, immediately flush skin or eyes with cool water for at least 15 minutes. For eyes, call a physician. If swallowed, drink milk, egg whites, gelatin solution, or if these are not available drink large quantities of water. Call a physician. If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a poison center or doctor/physician

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

FOR INDUSTRIAL USE ONLY

CAUTION:

Keep out of reach of children. Avoid getting in eyes. In case of contact, flush thoroughly with water. If irritation occurs, see a doctor.

S i no puedes leer esta etiqueta o no entiendes como usar este producto No lo uses, contacta a tu supervisor.

START KLEEN

SK-250

ALWAYS READ LABEL AND CONSULT SDS BEFORE USE.

USAGE RATES:

Hard Surface foaming - 1/2 to 6 oz. per gallon of water at 120 to 140° F. Equipment foaming: - use 1 or 2 gallons in 50 gallons of water depending on the type and degree of soil.

Always follow with a potable water rinse.

Consult a StartKleen representative for exact usage and concentrations in your plant.

STARTKLEEN SOLUTIONS, LLC 193 Wall Street Rd., Gunter, TX 75058 (903) 207-1079

NET CONTENTS: SAMPLE LOT NUMBER:



FREIGHT CLASSIFICATION:

Corrosive Liquid, basic, Inorganic, N.O.S. (Contains Potassium Hydroxide, Sodium Hypochlorite), 8, UN3266, PG II

CORROSIVE

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage and disposal. Store in a cool, dry place no lower in temperature than 50° F or higher than 120° F. Do not reuse container. Triple rinse container and dispose in a sanitary landfill or by other procedures approved by state and local authorities.

> 24 Hour Emergency Phone Number: Infotrac 800-535-5053

/		
	HEALTH	3
	FLAMMABILITY	0
	REACTIVITY	1
	PERSONAL PROTECTION	С