

**DANGER:** Contains Metasilicate and Sodium Percarbonate. **DO NOT** mix with acids. Can cause eye and skin damage. Do not get in eyes, on skin, or on clothing. Harmful if swallowed. Wear goggles and rubber gloves when handling. Avoid contamination of food. Remove and wash contaminated clothing. Do not breathe dust/fume/gas/mist/vapors/spray and use in well-ventilated area

**SK-899** can be used on stainless steel surfaces.

**STATEMENT OF PRACTICAL TREATMENT:**

In case of contact, immediately flush skin or eyes with cool water for at least 15 minutes. For eyes, call a physician. If swallowed, drink milk, egg whites, gelatin solution, or if these are not available drink large quantities of water. Call a physician. If inhaled: remove victim to fresh air and keep at rest in a position comfortable for breathing immediately call a poison center or doctor/physician.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

**FOR INDUSTRIAL USE ONLY**

**CAUTION:**

Keep out of reach of children. Avoid getting in eyes. In case of contact, flush thoroughly with water. If irritation occurs, see a doctor.

**Si no puedes leer esta etiqueta o no entiendes como usar este producto. No lo uses, contacta a tu supervisor.**

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL PROTECTION	C

# SK-899

ALWAYS READ LABEL AND CONSULT SDS BEFORE USE.

**USAGE RATES:** Hard Surface cleaning- 1/2 to 2 oz. per gallon of water at 120 to 140° F. Equipment cleaning: - use 5 to 7 lbs. in 50 gallons of water depending on the type and degree of soil.

Always follow with a potable water rinse to remove residue.

Consult a StartKleen representative for exact usage and concentrations in your plant.

**STARTKLEEN SOLUTIONS, LLC**  
**193 Wall Street Rd., Gunter, TX 75058**  
**(903) 207-1079**

NET CONTENTS:  
LOT NUMBER:

**STORAGE AND DISPOSAL:**

Do not contaminate water, food, or feed by storage and disposal. Store locked in a cool, dry place no lower in temperature than 50° F or higher than 120° F. Do not reuse container. Triple rinse container and dispose in a sanitary landfill or by other procedures approved by state and local authorities.

**24 Hour Emergency Phone Number:**  
**Infotrac: 800-535-5053**

**FREIGHT CLASSIFICATION:**  
UN1759, Corrosive Solid, N.O.S.  
(Sodium metasilicate), 8, PG III

# UN1759

